


2G11 series

Energy saving
and environmental protection


RD-2G11-225-10W



Real Power	10W
Light Source	2835 SMD
Lumen	1000Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC




RD-2G11-320-13W



Real Power	13W
Light Source	2835 SMD
Lumen	1300Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC




RD-2G11-410-15W



Real Power	15W
Light Source	2835 SMD
Lumen	1500Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC




RD-2G11-535-20W



Real Power	20W
Light Source	2835 SMD
Lumen	2000Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC




RD-ALY7-10W



Real Power	10W
Light Source	94 pcs 2835
Lumen	1000Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC



RD-E26-CP-8W



Real Power	8W
Light Source	SMD
Lumen	1020Lm
Color Temperature	3000/4000K
Beam Angle	300°
Material	Ceramic+PC
CRI	Ra>80
Voltage	120V AC




Attention:

- Lifespan of the bulbs will be effected while working ambient temperature that higher 45°C/113°F.
- The inner space of enclosed fixtures should be 5 times bigger than the size of the bulbs.
- The dimming level for dimmable products would be under a certain dimmer, it is better to take samples for testing the dimming function.

E Series LEDs




RD-E14/17-CP-6W-D



	E12	E14	E17
		✓	✓

Real Power	4.8W
Light Source	64pcs 2835SMD
Lumen	500Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	110/220V AC


RD-E14-CP-5W



Real Power	5W
Light Source	75pcs 2835SMD
Lumen	420Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC




RD-E12-3W-SG



Real Power	2.5W
Light Source	32pcs 2835SMD
Lumen	220Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC




RD-E12/14/17-FB-3W



	E12	E14	E17
	✓	✓	✓

Real Power	2.5W
Light Source	Filament LEDs
Lumen	280Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC


RD-E12/14-T26-1.5/2W



	E12	E14	E17
	✓	✓	

Real Power	1.2/1.8W
Light Source	2/4pcs Filament LEDs
Lumen	150/260Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC

RD-E12/14-C-1.5W



	E12	E14	E17
	✓	✓	

Real Power	1.5W
Light Source	4pcs 2835SMD
Lumen	80Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC

Attention:

- Lifespan of the bulbs will be effected while working ambient temperature that higher 45°C/113°F.
- The inner space of enclosed fixtures should be 5 times bigger than the size of the bulbs.
- The dimming level for dimmable products would be under a certain dimmer,it is better to take samples for testing the dimming function.


T-Bulbs


RD-T22-GS-1W


Real Power	1W
Light Source	SMD Customized LEDs
Material	Aluminum+PC
Lumen	100Lm
Color Temperature	2700-6500K
Base	E14
CRI	Ra>80
Voltage	120/230V AC


RD-T25-CP-1.5W


Real Power	1.5W
Light Source	SMD Customized LEDs
Material	Aluminum+PC
Lumen	100Lm
Color Temperature	2700-6500K
Base	E14
CRI	Ra>80
Voltage	120/230V AC


RD-T25-CP-2.5W


Real Power	2.5W
Light Source	SMD Customized LEDs
Material	Aluminum+PC
Lumen	210Lm
Color Temperature	2700-6500K
Base	E14
CRI	Ra>80
Voltage	120/230V AC


RD-T35-CP-5W


Real Power	5W
Light Source	SMD Customized LEDs
Material	Aluminum+PC
Lumen	450Lm
Color Temperature	2700-6500K
Base	E14/27
CRI	Ra>80
Voltage	120/230V AC


RD-T38-CP-8W


Real Power	8W
Light Source	SMD Customized LEDs
Material	Aluminum+PC
Lumen	800Lm
Color Temperature	2700-6500K
Base	E27
CRI	Ra>80
Voltage	120/230V AC


RD-T41-CP-9W


Real Power	9W
Light Source	SMD Customized LEDs
Material	Aluminum+PC
Lumen	900Lm
Color Temperature	2700-6500K
Base	E27
CRI	Ra>80
Voltage	120/230V AC



Attention:


- Lifespan of the bulbs will be effected while working ambient temperature that higher 45°C/113°F.
- The inner space of enclosed fixtures should be 5 times bigger than the size of the bulbs.
- The dimming level for dimmable products would be under a certain dimmer,it is better to take samples for testing the dimming function.

T-Bulbs



Use high performance LED chip,
long time use, brightness still

RD-T38-CP-12W



Real Power	12W
Light Source	SMD Customized LEDs
Material	Aluminum+PC
Lumen	1000Lm
Color Temperature	2700-6500K
Base	E27
CRI	Ra>80
Voltage	120/230V AC




RD-T44-CP-12W



Real Power	12W
Light Source	SMD Customized LEDs
Material	Aluminum+PC
Lumen	1200Lm
Color Temperature	2700-6500K
Base	E27
CRI	Ra>80
Voltage	120/230V AC



RD-T50-CP-12W



Real Power	12W
Light Source	SMD Customized LEDs
Material	Aluminum+PC
Lumen	1200Lm
Color Temperature	2700-6500K
Base	E27
CRI	Ra>80
Voltage	120/230V AC



RD-T60-CP-15W



Real Power	15W
Light Source	SMD Customized LEDs
Material	Aluminum+PC
Lumen	1500Lm
Color Temperature	2700-6500K
Base	E27
CRI	Ra>80
Voltage	120/230V AC



Attention:

- Lifespan of the bulbs will be effected while working ambient temperature that higher 45°C/113°F.
- The inner space of enclosed fixtures should be 5 times bigger than the size of the bulbs.
- The dimming level for dimmable products would be under a certain dimmer,it is better to take samples for testing the dimming function.