


LED GU6.5/GX5.3 Bulb




RD-2SMD-GU6.5-108/144-A




Real Power	10W/15W
Light Source	SMD5630 Epistar
Lumen	1000Lm/1500Lm
Color Temperature	3000K/4000K/6000K
CRI	Ra>80
Voltage	85-265VAC PF>0.9
Size	Φ25x88mm/ 112mm
Dimmable	optional 110/230V

RD-2SMD-GX53-5W-C(3 COLORS)




Real Power	5W
Light Source	SMD2835 Epistar
Lumen	500Lm
Color Temperature	3000K/4000K/ 6000K (3 colors change)
CRI	Ra>80
Voltage	85-265VAC
Size	Φ75x25mm

RD-2SMD-GX53-5W/7W/9W/11W-B



Real Power	5W/7W/9W/11W
Light Source	SMD2835 Epistar
Lumen	500Lm/700Lm/ 900Lm/1100Lm
Color Temperature	3000K/4000K/ 6000K
CRI	Ra>80
Voltage	85-265VAC
Size	Φ75x25mm
Dimmable	optional 110/230V

RD-2SMD-GX53-3W/5W-A



Real Power	3W/5W
Light Source	SMD2835 Epistar
Lumen	300Lm/500Lm
Color Temperature	3000K/4000K/ 6000K
CRI	Ra>80
Voltage	85-265VAC
Size	Φ75x25mm
Dimmable	optional 110/230V




Attention:

- ⊙ Lifespan of the bulbs will be effected while working ambient temperature that higher 45°C/113°F.
- ⊙ The inner space of enclosed fixtures should be 5 times bigger than the size of the bulbs.
- ⊙ The dimming level for dimmable products would be under a certain dimmer,it is better to take samples for testing the dimming function.

LED GX23/G23/2GX7/2G7/GX10/2G10 Bulb




RD-2SMD-PL-18/28/35/48/60/72-A




Real Power	4W/6W/8W/8W/ 10W/12W
Light Source	SMD2835 Epistar
Lumen	400Lm/600Lm/800Lm/ 800Lm/1000Lm/1200Lm
Color Temperature	3000K/4000K/ 6000K
CRI	Ra>80
Voltage	85-265VAC
Size	21x31.5x127mm/ 137mm/237mm/167mm/ 207mm/237mm
Beam angle	200°

RD-2SMD-PL-18/28/35/48/60/72-B



Real Power	4W/6W/8W/8W/ 10W/12W
Light Source	SMD2835 Epistar
Lumen	400Lm/600Lm/800Lm/ 800Lm/1000Lm/1200Lm
Color Temperature	3000K/4000K/ 6000K
CRI	Ra>80
Voltage	85-265VAC
Size	19x37x116mm/ 156mm/226mm/21x31.5 x156mm/206mm/226mm
Beam angle	200°

RD-2SMD-PL-48/72/96-B



Real Power	10W/15W/18W
Light Source	SMD2835 Epistar
Lumen	1000Lm/1500Lm/ 1800Lm
Color Temperature	3000K/4000K/ 6000K
CRI	Ra>80
Voltage	85-265VAC
Size	90x22x130mm/ 170mm/220mm



Attention:

- ⊙ Lifespan of the bulbs will be effected while working ambient temperature that higher 45°C/113°F.
- ⊙ The inner space of enclosed fixtures should be 5 times bigger than the size of the bulbs.
- ⊙ The dimming level for dimmable products would be under a certain dimmer, it is better to take samples for testing the dimming function.